

**UNITED STATES PATENT APPLICATION**

**OF**

**JYH-CHENG CHEN**

**AND**

**TAO ZHANG**

**FOR**

**DISTRIBUTED SMOOTH HANDOFF USING SHADOW ADDRESSES**

**IN IP-BASED BASE STATIONS**

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
218

**DISTRIBUTED SMOOTH HANDOFF USING SHADOW ADDRESSES  
IN IP-BASED BASE STATIONS**

5 CROSS-REFERENCE TO RELATED APPLICATION

This application is a non-provisional application of provisional application  
Serial No. 60/281,309 filed April 4, 2001.

BACKGROUND OF THE DISCLOSURE

10 Field of the Invention

This invention relates generally to a wireless-to-wireline and wireless-to-  
wireless communication system that is composed of wireless access networks  
15 interconnected via a wireline IP (Internet Protocol) network, and, more particularly, to  
methodologies and concomitant circuitry for effecting soft handoff in the wireless portion  
of the system.

20 2. Description of the Background Art

Today, many different wireless systems exist, ranging from indoor  
wireless LANs (Local Area Networks) to outdoor cellular systems. Generally, the  
numerous wireless systems are not compatible with each other, making it difficult to  
25 roam from one system to another. Although there have been attempts to unify third-  
generation wireless systems, incompatible systems are expected to co-exist in the future.  
Furthermore, wireless LANs and cellular wireless systems are being developed

independently, and such systems are also evolving independently. So far, no wireless technology has emerged as a common and long-term universal solution.

IP (Internet Protocol), which is already a universal network-layer protocol for packet networks, is rapidly becoming a promising universal network-layer protocol for wireless systems. An IP terminal, with multiple radio interfaces, can roam between different wireless systems if they all support IP as a common network layer. Unlike today's wireless systems in which Radio Access Networks (RANs) are mostly proprietary, IP provides an open interface and promotes an open market. IP will also enable widely adopted and rapidly growing IP-based applications to run over wireless networks. Moreover, distributed, autonomous IP-based wireless base stations have the potential of making the wireless systems more robust, scalable, and cost effective.

There are, however, many challenges to realizing distributed all-IP wireless networks. For the sake of specificity in discussing these challenges as well as pointing out problem areas, reference is made to FIG. 1. The depiction of network 100 in FIG. 1 illustrates an exemplary configuration of a network that uses IP-based wireless base stations (designated iBSs). The coverage area of the wireless network is defined by a multiplicity of cells (e.g., cells 101, 102, 103). The geographical area covered by each wireless base station is referred to as a cell (e.g., iBS 111 serves cell 101, and so forth). When mobile station 104 moves from one cell (e.g., cell 101 originally) into the overlapping regions (e.g., overlap of cells 101 and 102) of the coverage areas of multiple base stations, base station 111 may perform a "handoff" of mobile station 104 to base

station **112**. Handoff is a process whereby a mobile station communicating with one wireless base station is switched to another base station during a session. Overlap regions **117** and **118** are coverage areas where handoff is effected. For example, as mobile station **104** moves into region **117** while roaming in cell **101**, the radio signal strength from iBS 2 (depicted by reference numeral **115**) may be greater than the radio signal strength (**114**) from iBS 1, so handoff is warranted to maintain the quality of the established session.

Among the key challenges in a distributed all-IP wireless network is how to support “soft handoff”. As suggested above, handoff is the process that allows a mobile station's session-in-progress to continue without interruption when a mobile station (MS) moves from one wireless cell to another. Soft handoff is a form of handoff whereby a mobile station can start communication with the target base stations without interrupting the communication with the serving base station. Thus, soft handoff allows a MS to communicate with multiple base stations (BSs) simultaneously. In particular, soft handoff has been shown to be an effective way for increasing the capacity, reliability, and coverage range of CDMA-based wireless networks. Soft handoff also provides more time for carrying out the handoff procedure.

Soft handoff in a CDMA-based wireless system is the focus of the subject matter of the present invention. In Code Division Multiple Access (CDMA) radio systems, a narrowband user message signal is multiplied by a very large bandwidth signal called the spreading signal. The spreading signal is a pseudo-noise code sequence that

has a communication signal rate which is orders of magnitudes greater than the data rate of the user message signal. All users in a CDMA system may transmit simultaneously. Each user has its own pseudorandom code for coding its own message signal – each code is approximately orthogonal to all other codes. A receiver is assigned a code to detect a

5 desired user message signal, and performs a time correlation operation to detect only the specific assigned code. All other codes appear as noise due to de-correlation. CDMA is effective in wireless systems because a receiver can be assigned a multiplicity of codes to detect message signals from a corresponding multiplicity of transmitters, thereby engendering the soft handoff process.

10 An IP router is an IP network device that runs IP layer routing protocol (e.g., OSPF and BGP) and forwards IP packets. The running of a routing protocol decides the “routing policy”, and the forwarding of IP packets realizes the “routing mechanism”. IP packets arriving from the wireline IP network (121) at a given base station (e.g., iBS

15 111 over wireline path 122 or iBS 112 over path 123) can be routed by the routing mechanism of the base station to mobile station 104 (or other appropriate wireline devices that connect directly to the base station).

20 Today, the only known approach to designing an IP-based base station is to add (or connect) radio transmission and receiving equipment directly onto an IP router (131). Such a design, however, has a potentially serious shortcoming. In particular, the mobile stations served by different base stations must belong to different IP subnets, that is, the design forces the mobile stations in different cells to be on different IP subnets.

(Here, a subnet is used in the sense defined by an IP address, which has the form, for example, “w.x.y.z” (e.g., 129.3.2.14), wherein “w.x” is the network address (129.3), “y” (2) is the subnet address for a device associated with the given network, and “z” (14) is the host address for a device associated with the given network/subnet, such as a mobile terminal or a base station. In terms of FIG. 1, iBS 1 may be assigned the subnet address 2, whereas mobile station 104 may have the host address 14.) Suppose, for the sake of argument, that a mobile station is served by two base stations belonging to the same IP subnet S. Then, both iBSs (IP routers) will advertise to other routers in the overall network that they can reach all the hosts on subnet S. However, each iBS can only reach a subset of the hosts on subnet S (i.e., the set of hosts being currently served by the base station). This means that other routers will not be able to determine which base station should receive a packet destined for a host on subnet S. In other words, packets may be delivered to the wrong base station and consequently cannot reach the destined host.

The fact that mobile stations (MSs) in different cells belong to different IP subnets suggests that an MS may have to change its IP address every time it moves into a new cell. Changing IP address usually takes a long time using today’s methods for dynamic IP address assignment (e.g., the Dynamic Host Configuration Protocol or DHCP). When certain IP-layer mobility management mechanisms are used (e.g., SIP-based mobility management), a change of IP address can also mean that the old session may need to be modified, or new SIP sessions may have to be established.

Having to change IP addresses when moving from one cell to another also

makes soft handoff more difficult to implement. For example, if an MS has to use different IP addresses to receive IP packets from different iBSs, IP packets coming to the MS from different iBSs will not be identical because they carry different IP destination addresses. Consequently, copies of the same packets from different base stations may not be correctly combined by the MS's radio system.

Recently, methods (e.g., HAWAII, Cellular IP) have been proposed to enable MSs to move within a domain of multiple IP subnets without having to change their IP addresses. These methods, however, typically require complex IP-layer signaling and significant changes to the IP routers in the domain. Furthermore, these methods have not considered how to solve the data content synchronization problem.

From another viewpoint, in today's circuit-switched CDMA networks such as IS-95, a centralized Selection and Distribution Unit (SDU) is responsible for data distribution in the forward direction (from BS to MS). The SDU creates and distributes multiple streams of the same data over layer-2 circuits to multiple BSs that in turn relay the data to the MS. The MS's radio system (typically working below the IP layer) collaborates with the BSs to synchronize the radio channel frames and combine the radio signals received from different BSs to generate a single final copy of received data. The SDU helps ensure data content synchronization by ensuring that the matching layer-2 frames sent to different base stations contain copies of the same data. In the reverse direction (from MS to BS), the MS ensures that the matching layer-2 frames sent to different BSs contain copies of the same data. The SDU then selects one of the frames

received from different base stations as the final copy of the data.

Accordingly, as evidenced by the foregoing discussion, achieving soft handoff among distributed iBSs introduces several new technical problems that cannot be solved readily by the mechanisms developed for today's centralized circuit-switched wireless networks.

One problem already alluded to is loss of data content synchronization. With distributed iBSs, centralized control entities, such as the SDU in circuit switched wireless networks, will no longer exist. Consequently, even though the CDMA radio system is capable of synchronizing the link and physical layer frames on the radio channel, it cannot, on its own, guarantee that the matching frames from different base stations will carry copies of the same data. For example, IP packets can be lost on their way to the MS, creating random gaps in the packet streams received by the MS from different iBSs. Furthermore, copies of the same data may arrive at the MS at different times due to the random delays suffered by the packets. Random gaps and delays can lead to a loss of data content synchronization. Suppose that packet X is lost at iBS 1 (due to, for example, buffer overflow) but is not lost at iBS 2. Then, another totally unrelated packet Y from iBS 1 and packet X from iBS 2 may arrive at the MS at the same time and the MS's radio system will not be able to tell that they are not copies of the same data and will hence erroneously combine X with Y.

Another problem is how to support soft handoff, which requires a mobile



station to receive identical copies of the same data from multiple base stations simultaneously. When the mobile stations served by different base stations belong to different IP subnets, complex IP-layer signaling capabilities (e.g., IP multicast) have conventionally be required to direct copies of the same IP packets via multiple base stations to the mobile station. Furthermore, copies of the same IP packet arriving from different base stations to the mobile station will not be identical because these packets will carry different destination IP addresses. This makes it impossible for the mobile station's radio system to combine the signals from different base stations into a single copy of data.

The art is devoid of a methodology and concomitant systems that effect soft handoff in an all-IP wireless network that uses autonomous iBSs in a configuration having the following characteristics that differentiate the configuration from existing wireless networks: (a) the iBSs use IP protocols for both signaling and transport of user traffic. For example, they may route/forward IP packets based on information carried in the IP headers, perform IP-layer signaling, mobility management and Quality of Service (QoS) management functions; (b) the iBSs function autonomously. There is no centralized signaling and control over the behaviors of the iBSs; (c) the iBSs are interconnected via an IP network which could have arbitrary network topology such as bus, ring, star, tree, etc.; and (d) the cells (a cell is a geographical radio coverage area of a BS) can be arranged in any arbitrary configuration.

SUMMARY OF THE INVENTION

These shortcomings and other limitations and deficiencies are obviated, in accordance with the present invention, by assigning an alias or shadow address to a mobile station that is compatible with the link layer address of the wireline subnet which delivers packets to the mobile station via base stations connected to the wireline subnet, storing the shadow address in the base stations that serve the mobile station during smooth handoff, and using the shadow address of the mobile station for packets communicated to the mobile station via the base stations from a sending device coupled to the subnet.

Broadly, in accordance with a method aspect of the present invention, a method for carrying out smooth handoff as a mobile station roams from a first base station to a second base station both served by a wireline subnet having a link layer different than the link layer of the wireless network serving the mobile station, includes: (a) storing a shadow address in the first base station and the second base station, the shadow address corresponding to the mobile station and having a format compatible with the link layer of the wireline subnet; (b) transmitting a frame containing the packet from the sending device over the wireline subnet using the shadow address as the link layer destination address of the packet; and (c) processing the frame received from either the first base station or the second base station in the mobile station.

Broadly, in accordance with a system aspect of the present invention, circuitry for carrying out smooth handoff as a mobile station roams from a first base

station to a second base station both served by a wireline subnet having a link layer different than the link layer of the wireless network serving the mobile station, includes:

(a) a storage device for storing a shadow address in the first base station and the second base station, the shadow address corresponding to the mobile station and having a format compatible with the link layer of the wireline subnet; (b) a receiver for receiving a frame containing the packet transmitted from the sending device over the wireline subnet using the shadow address as the link layer destination address of the packet; and (c) a processor for processing the frame received from either the first base station or the second base station in the mobile station.

#### BRIEF DESCRIPTION OF THE DRAWING

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

FIG. 1 depicts a wireline-wireless system composed of autonomous base stations serving mobile stations;

FIG. 2 depicts a system composed of both wireline and wireless networks wherein base stations on a subnet serve mobile stations using their shadow addresses;

FIGS. 3A and 3B depict a generic IP packet and an IP packet having a mobile station as a destination device, respectively;

FIGS. 3C and 3D depict a generic Ethernet frame and an Ethernet frame having the shadow address of the mobile station as an Ethernet destination address, respectively;

FIG. 4 depicts a system composed of both wireline and wireless networks wherein a multiplicity of base stations on the same subnet send multiple copies of a packet to a roaming mobile station to carry out soft handoff;

FIG. 5 depicts base station processing in terms of conventional physical layer, link layer, and IP layer protocol stacks while using shadow addresses of mobile stations;

FIG. 6 depicts the arrangement of a base station in terms of only the conventional physical layer and link layer protocol stacks to process shadow addresses of mobile stations;

FIG. 7 depicts the processing by a base station that performs the routing mechanism without changing the routing policy fostered by shadow addresses;

FIG. 8 is a flow diagram depicting the process of assigning a shadow address to a mobile station;

FIG. 9 is a flow diagram depicting the process by which a mobile station associates with a new base station using physical layer information and link layer messages;

FIG. 10 is a flow diagram depicting the process of assigning a shadow address by a base station upon first power-up of a mobile station;

FIG. 11 is a flow diagram depicting the process of assigning a shadow address by a candidate base station for a powered-up mobile station handled by a serving base station;

FIG. 12 is a flow diagram depicting the process of deleting a shadow address from a watch list;

FIG. 13 is a pictorial representation of a mobile station roaming from one cellular region served by one subnet to another cellular region served by another subnet during the process of soft handoff;

FIG. 14 is a flow diagram depicting an illustrative technique for generating entries for the Packet Duplication table, including a multiplicity of IP layer address associated with a roaming mobile station

FIG. 15 is a time diagram depicting the time relationship of packets and frames as delivered by two base stations to a mobile receiver involved in soft handoff across subnets;

FIG. 16 is a pictorial representation illustrating recovery of synchronization for matchable packet streams during soft handoff; and

FIG. 17 is a flow diagram depicting the algorithm to regain synchronization for matchable packet streams during soft handoff.

## DETAILED DESCRIPTION

### 1. Soft Handoff Within a Subnet

#### 1.1. "Shadow" Address

As illustrated by system **200** in FIG. 2, which is a recast version of system **100** of FIG. 1 for purposes of highlighting the principles of the present invention, on one side of iBS 1 and iBS 2 (**111** and **112**, respectively) is wireline IP network **201**. Wireline IP network **201** serves as one subnet used to interconnect iBS 1 and iBS 2 with router **131**. For sake of specificity, but without loss of generality, wireline IP network **201** is

presumed to be an Ethernet. Router **131** is also coupled to other IP networks, such as the Internet, via another port to deliver packets to and from wireline IP network **201** over path **132**. On the other side of iBS 1 and iBS 2 is a wireless network represented, in part, by wireless radio path **114** linking MS **104** with iBS 1. Thus, there is a clear

5 demarcation between the wireline and wireless aspects of system **200**, which is depicted in FIG. 2 by the Ethernet and non-Ethernet portions of system **200**.

It is also readily appreciated that, whereas the sending device was exemplified as being coupled, for example, into wireline network 201 from a device

10 propagating a packet through router 131 of FIG. 2, it is clear that the principles of the present invention also apply for a wireless sending device that use a link layer addressing scheme which is compatible with the link layer of the subnet. Accordingly, both cases are covered in the description by stating that the sending device is “coupled to” the wireline subnet, thereby covering (but not being limited to) both direct connection or

15 wireless coupling to the subnet.

To understand the importance of the separation between the wireline and wireless sides of the base stations, consider the ramifications of a single IP subnet serving multiple iBSs, as illustrated in FIG. 2. Generically, when a device (e.g., router, iBS, or host) on the wireline IP subnet wants to send an IP packet to a mobile station, the sending

20 device, by convention, normally determines the layer-2 address that should be used to send the IP packet over the wireline subnet to the base station handling the mobile station. But, when the mobile station is using a different layer-2 protocol that is incompatible with the layer-2 protocol used on the wireline subnet, the sending device

cannot use the layer-2 address of the mobile to send IP packets over the wireline subnet. This will be the case, for example, when the wireless network uses CDMA technologies that have a different format for the layer-2 address than that on the wireline subnet (such as Ethernet).

5

To circumvent this difficulty and to ensure that a sending device can direct the packet to the right base station, consider first deploying the wireline layer-2 address (e.g., MAC address in the case of Ethernet) of the destination base station as an alias for the mobile station and, accordingly, the sending device would forward the packet to the destination base station as the proxy for the mobile station. Then, the base station can use, in turn, IP-layer and/or other layer information to determine to which mobile station the packet should be sent. This is only part of the solution, however, because in this scenario only a single base station serves the mobile station. To carry out soft handoff, it is necessary that multiple base stations relay copies of the same packet to the mobile station which would be difficult in the above scenario, that is, sending a packet to only a single base station's wireline layer 2 address.

10

15

20

Consider now an extension to the above approach whereby a so-called "shadow address" is utilized. With the shadow address approach, besides the unique wireless layer-2 address normally allocated to each mobile station, a unique wireline layer-2 address is also assigned to the mobile station. Since the mobile station may be using a different layer 2 than the wireline network, the wireline layer-2 address assigned to the mobile station may have no meaning to the mobile station and cannot be used by

the mobile station for any other purposes. However, the wireline layer-2 address assigned to the mobile station can be advantageously used by a base station to determine which layer-2 frame arriving from the wireline network should be accepted by the base station and, if accepted, to pass the IP packet contained in the layer-2 frame to the IP layer in the base station for further processing. The IP layer of the base station then uses the information in the IP header of the incoming IP packet to determine which radio interface on the base station the packet should be sent to. In essence, the wireline layer-2 address assigned to a mobile station can be viewed as a “shadow” that the mobile station casts on the wireline layer 2. For this reason, the wireline layer-2 address assigned to a mobile station will be referred to as the shadow wireline layer-2 address of the mobile station, or “shadow address” for short.

Each base station maintains a “watch list” similar to that in Table 1. The field denoted “MS’s IP Address” contains the IP address which is assigned to the mobile station in the subnet. The field denoted “MS’s Shadow Address” is the shadow wireline layer-2 address. Table 1 shows the address in the format of the IEEE 802.3 MAC address which is the most popular link layer or layer 2 for a LAN (layer 2 and link layer are used interchangeably in the sequel without loss of generality). The field denoted “MS’s Link Layer Address” is the real wireless link layer address of the mobile station. It could be the link layer address for any one of many different standards, such as cdma2000, WCDMA, Bluetooth, and so forth.



MS's IP Address	MS's Shadow Address	MS's Link Layer Address
128.33.22.121	00:60:1D:03:E7:E1	xxxxxx
129.55.32.131	E1:E7:03:1D:60:01	yyyyyy
...	...	...
...	...	...

**Table 1**

5           The shadow address may be assigned to a mobile station dynamically when the mobile station powers up and accesses the wireless network for the first time. Or, it can be configured in the mobile station prior to the first time it is powered, that is, each mobile station may be assigned a shadow address in addition to a real link layer address. Shadow address assignment will be discussed in more detail below when flow diagrams are presented.

#### 1.2. Use of Shadow Address by a Base Station to Relay a Packet

Each base station uses the shadow address created for each mobile station to help relay an IP packet between the wireless and the wireline networks. The wireline interface of each base station examines the layer-2 destination address of each layer-2 frame arriving from the wireline network. If the destination layer-2 address matches any shadow address in its watch list, the base station accepts the frame, takes the IP packet out from the frame, and passes the IP packet to the base station's IP layer for further processing. For ease of discussion, the term "matching frames" is used to refer to a layer-2 frame whose destination layer-2 address matches one of the shadow addresses currently in the base station's watch list. If the IP packet is destined for one of the mobile stations currently served by the base station, the IP layer forwards the IP packet to the destination

mobile station. If the IP packet is not destined for either any mobile station currently being served by the base station or the base station itself, the IP layer may ignore the packet.

5                   When any device on the local wireline IP subnet wants to send a first IP  
packet to a mobile station, the sending device must first determine the shadow wireline  
layer-2 address of the destination mobile station. The sending device can do this, for  
example, by using the well-known, conventional Address Resolution Protocol (ARP)  
designed for the wireline IP network. In particular, the sending device will broadcast an  
10   ARP REQUEST packet over the local IP subnet. The base station that has the shadow  
layer-2 address of the destination mobile station in its watch list will respond to the ARP  
REQUEST with the shadow layer-2 address of the destination mobile station. The  
shadow wireline layer-2 address will then be used by the sending device on the local IP  
wireline network to send a packet to the mobile station via the base station responding to  
15   the ARP REQUEST. In addition, when the shadow layer-2 address of a destination  
mobile station is in the watch list of multiple base stations, all of the base stations may  
respond to the ARP REQUEST. These responses will contain the same shadow address of  
the destination mobile station. The import of multiple base stations having the mobile  
station on their watch lists will be elaborated upon shortly.

20

To illustrate the foregoing discussion concretely, consider the IP packet of  
FIG. 3A composed generally an IP payload 303 and an IP header which is composed of,  
among other information, the IP destination address 301 and IP source address 302. In

addition, suppose the packet is originated by an IP sending device coupled to path **132** of FIG. 2, and the packet is destined for mobile station **104** served by iBS 1. Thus, the IP destination address is the IP address of the mobile station **104** -- this particular packet is shown in FIG. 3B. In order for the sending device to decide how to encapsulate the

5 packet at layer 2, the sending device propagates an ARP REQUEST asking for the layer-2 address that corresponds to the IP address of the mobile station (e.g. 128.33.22.121 in Table 1) over wireline IP network **201**, which again for concreteness, is presumed to be an Ethernet. The ARP REQUEST reaches iBS 1, and iBS 1 notes that this IP address is in its watch list and it is associated with mobile station **104**. In response to the ARP  
10 REQUEST, iBS 1 sends the shadow address (00:60:1D:03:E7:E1) of mobile station **104** to the sending device. The shadow address, which is an actual wireline layer-2 address for wireline **201**, can then be used by the sending device to encapsulate the packet into an Ethernet frame. A generic Ethernet frame is shown in FIG. 3C and has, besides the packet fields, the Ethernet destination address **311** and the Ethernet source address **312**.

15 In FIG. 3D, the actual Ethernet frame containing the given packet is shown; the Ethernet destination address is the shadow address of mobile station **104**.

As the Ethernet frame of FIG. 3D propagates over wireline **201**, the frame is detected by iBS 1. Then iBS 1, via its watch list, recognizes the shadow address in the  
20 Ethernet frame as one being served by iBS 1. Accordingly, iBS 1 handles the Ethernet frame by stripping off the layer-2 information, including fields **311** and **312**, and passes the IP packet to the IP layer processing of iBS 1. Processing at the IP layer will be discussed in more detail in the sequel.

The layer-2 frames going out from a base station to the wireline IP network may set its source layer-2 address to the shadow layer-2 address of the source mobile station (the mobile station that originated this packet) or the layer-2 address of the base station.

5

### 1.3. Base Stations Use of Shadow Addresses to Simultaneously Relay Copies of the Same Packet to a Mobile in Soft Handoff State

Arrangement **400** of FIG. 4 illustrates how multiple base stations can use the shadow layer-2 address of a mobile station to simultaneously relay copies of the same IP packet to the mobile station to carry out soft handoff.

Suppose initially that mobile station **104** is registered with iBS 1 (**111**), and that mobile station (MS) **104** has the parameters listed in row 1 of Table 1 above, that is, the IP address of the MS **104** is 128.33.22.121 and the shadow address is 00:60:1D:03:E7:E1 (which will be called  $MAC_{104}$  for short). Watch list 1 (**401**) in iBS 1 is, for illustrative purposes, that exemplified by Table 1; accordingly, the shadow address of MS **104** is in watch list **401**. When mobile station **104** first starts communication with new base station iBS 2 (**112**) as it roams into the overlap of the cellular regions, iBS 2 will insert  $MAC_{104}$  into its watch list, shown as watch list 2 (**402**). Many ways exist for the new base station to learn the shadow address of the MS and will be discussed in greater detail later. Exemplary contents for watch list **402** are listed in Table 2 below; the third row contains information about MS **104**. From this point in time, iBS 2 will accept a layer-2 frame coming from the wireline network that carries  $MAC_{104}$  as the destination layer-2 address and will send the packet carried in this frame to the IP layer on iBS 2 for further processing.

MS's IP Address	MS's Shadow Address	MS's Link Layer Address
...	...	...
128.44.12.111	F1:F7:04:2D:70:03	ZZZZZZZZ
128.33.22.121	00:60:1D:03:E7:E1	XXXXXX
...	...	...

Table 2

Since both base stations iBS 1 and iBS 2 now have  $MAC_{104}$  in their watch lists, they will both accept layer-2 frames destined for  $MAC_{104}$  and forward the IP packet carried in these frames to the mobile station simultaneously, as exemplified by path **405** and path **406**, respectively. Path **405** delivers Ethernet frame **404** containing  $MAC_{104}$  and an embedded IP packet over IP subnet **201** to iBS 1 and, in turn, over a radio channel to MS **104**. Similarly, path **406** delivers IP frame **404** containing  $MAC_{104}$  and the embedded IP packet over IP subnet **201** to iBS 2 and, in turn, over a radio channel to MS **104**.

FIG. 5 illustrates the arrangement **500** of a base station in terms of conventional protocol stacks, namely, physical layers **501-1** and **501-2**, link or layer 2 layers **502-1** and **502-2** (e.g., receiving frames), and the IP layers **503** (e.g., receiving packets) to process the shadow wireline layer-2 address for a mobile station. Layers **501-1** and **502-1** are associated with the wireline side of the base station, whereas layers **501-2** and **502-2** are associated with the wireless side of the base station. By way of reiteration, the main purpose of shadow addresses is to enable the wireline interface of the base station to accept the layer-2 frames that arrive from wireline networks and are destined for mobile stations served currently by the base station with reference to its watch list.

The wireline interface of the base station will monitor all layer-2 frames that come from the wireline network and will accept any layer-2 frame whose destination layer-2 address matches the shadow address of any mobile station currently being served by the base station. As depicted in FIG. 5, there are two incoming frames labeled **511** and **521**,

5 respectively. It is presumed that only frame **512** has a layer-2 destination address that is in the watch list (**505**) for the base station. In effect, the watch list acts as a filter to select only those frames having a destination address which is either the base station layer 2 address or shadow addresses contained in the watch list. Once a layer-2 frame is accepted by the wireline layer 2, the IP packet (**522-1**) carried in the frame will be extracted and  
 10 passed to the IP layer forwarding engine **506** in IP layer **503** for any processing (e.g., QoS control) at the IP layer.

In particular, the IP address of the mobile station is known to the base station via, for instance, the contents of watch list exemplified by Table 1. Moreover, the  
 15 base station utilizes another table that maps radio channels to mobile stations; an illustrative table is shown by Table 3:

Radio Channel Number	MS's IP Address	MS's Link Layer Address
1	not assigned	...
2	128.33.22.121	xxxxxx
...	...	...
N	129.55.32.131	yyyyyy

**Table 3**

The IP address of mobile station **104**, as used throughout the discussion, is on the second row of Table 3, namely, 128.33.22.121. Radio channel 2 is presently serving mobile station **104**. Outgoing packet **522-2** from the IP forwarding engine, which is the counterpart to incoming packet **522-1** resulting from processing in IP forwarding engine **506**, is passed to layer 2 (**502-2**) for encapsulation. The frame format is that deployed by the radio system, and the destination address is determined from the mobile station's layer-2 address from watch list **505**. Finally, the layer 2 radio frame is propagated to mobile station **104** over wireless channel **114**.

A base station could also directly use the shadow addresses to determine to which mobile station a layer-2 frame arriving from the wireline network should be sent to and then send the layer-2 frame directly to the outgoing radio channel without IP-layer processing. This process is referred to as layer-2 switching, which means switching layer-2 frames from an incoming layer 2 to an outgoing layer 2 of a base station. In this mode, the base station is essentially functioning as a layer-2 bridge.

The arrangement **600** of FIG. 6 depicts this scenario. As in FIG. 5, an incoming frame is passed to layer 2 (**501-2**) whenever the layer-2 address of the incoming frame is in the watch list. Because the watch list has the necessary information to complete packet forwarding at layer 2, namely, the layer-2 wireline address (e.g., xxxxxx), the IP layer processing can be bypassed if desired. Again, the contents of Table 3 can be used to identify the mobile station by its layer 2 address (**606**), and encapsulate the frame propagated by radio channel **531** using the layer-2 wireless address (it is clear

that a simplified version of Table 3 is possible in this case, wherein only the first and third columns compose the simplified table). Note that the base station switches the payload of the incoming frame (e.g., IP packets in case of IP-based base station) rather than the entire incoming layer-2 frame. This is because wireless and wireline layer-2 protocols used in the network can be completely different and, consequently, the layer-2 header on the wireline network will become useless in the wireless network and vice versa.

#### 1.4. IP-Based Base Station Performs Routing Mechanism without Changing Routing Policy

One operational principle in accordance with the present invention is that each IP-based base station will act as an IP-layer forwarder, as alluded to in FIG. 5. Now referring to FIG. 7, there is shown a pictorial representation of the processing effected by a base station so that the routing mechanism based on shadow addresses does not require a change in the routing policy of a base station. In particular, in one operational mode, iBS 701 (representative of, say iBS 1 (111)) uses the information in the IP header of an incoming packet (e.g., IP 0) from wireline interface 722 and a routing table to determine where the packet should be sent, and then forwards the packets to the correct outgoing radio channel, i.e. iBS 701 station performs the IP routing mechanism. However, it is not required that a base station run IP routing protocols to change its routing table. For instance, IP forwarding engine 707 may determine that IP 0 is bound for MS 1 (711) and, accordingly, forwards IP 0 as outbound packet IP 1 to MS 1 via electronic/radio path 715 in radio interface 721 and radio path 713. A description similar to the above also applies to MS 2 (712).



### 1.5. Assignment and Processing of Shadow Addresses

There exist many ways for a new base station to learn about or assign the shadow address for a MS. For example, the iBSs may obtain the shadow address for a MS from a network server responsible for assigning shadow addresses. Alternatively, and the focus in accordance with the present invention, is the case wherein the iBSs themselves can be responsible for assigning shadow addresses to MSs. In this case, the MS may carry its own shadow address and pass it along to the new base station or the new base station may obtain a MS's shadow address from the serving base station.

By way of elucidating the details of a representative technique for assigning and using a shadow address which illustrates the methodology whereby the MS carries its shadow address, it is assumed in the following description that: the serving iBS assigns a shadow address to a MS; the MS passes its assigned shadow address to a new iBS; and when a MS's shadow address conflicts with any shadow address currently in use in the new cell, the new iBS will negotiate with the serving iBS to resolve the conflict.

An illustrative technique for assigning a shadow address to a mobile station by the iBS is depicted by flow diagram **800** of FIG. 8. The process starts with processing block **805** when the MS is powered up in a wireless region. Next, as evidenced by processing block **810**, the MS scans to locate a candidate iBS to serve the MS based upon the value of the signal-to-noise ratio (SNR) using a so-called "scanning algorithm" (the scanning algorithm is conventional to a mobile service environment, and it is carried out at the "physical" layer level). Once a candidate iBS is located, processing

by block **815** is invoked whereby the MS sends a “request to associate” with the candidate iBS; the request includes the MS identifier (as described below) which is unique to the MS. Next, via processing block **820**, the candidate iBS assigns a shadow address to the MS which is compatible with the wireline link layer of the subnet to which the iBS is connected. The MS may also need to obtain an IP address if it does not already have one (e.g., when the MS tries to use IP services for the first time) or if it needs a new IP address (e.g., when it moves into a new IP subnet). The MS may use any existing methods (e.g., DHCP) to obtain an IP address. In terms of the example used to fill the second row of Table 2, the IP address assigned is 128.44.12.111 and the shadow address assigned is F1:F7:04:2D:70:03. Processing block **825** is executed so that the candidate iBS stores the shadow address, IP address, and the wireless link layer address of the MS in the watch list and the candidate iBS becomes the serving iBS. Finally, as per processing block **830**, the MS stores the IP address and the shadow address to be used during packet processing, as discussed in more detail later.

In the foregoing the term MS identifier was used, and the following is a brief description of one realization of such an identifier. A wireless network interface card (NIC) of a MS is assigned a unique address by the manufacturer of the particular NIC – this address is called the “MS MAC address” or, equivalently, the “MS identifier”, where MAC is the acronym for Medium Access Control; the MAC Address is utilized at the “link” layer in the wireless network portion of a wireline/wireless network. Each MS identifier usually has 48 bits which can be formatted as follows: “B1:B2:B3:B4:B5:B6”, where B1, B2, ... is each one byte. Also, since each byte can be treated as containing

two 4-bit nibbles, the MS identifier is such that each nibble can be expressed in hexadecimal. Thus, a typical MS identifier might be: “18:00:20:E8:42:F6”, and it is unique to a particular MS, so it can be used as a universal identifier. In the foregoing description, the symbolism “xxxxxx” was used to denote the MS identifier, which must

5 be compatible with all iBSs that the MS will roam to in the wireless network.

Next, the process by which the MS interacts with a new base station to convey shadow address information pertaining to the MS is considered in overview fashion in FIG. 9. With reference to FIG. 9, there is shown flow diagram **900** for this process; the flow diagram emphasizes those differences over conventional processing brought about by the use of a shadow address. The process starts with processing block **905** whereby the MS is presumed to be powered up and being served by a base station (referred to as the “old base station” below), as covered by FIG. 8. The MS continuously monitors, via decision block **910**, the incoming signal strength of the old base station to

10 determine if the SNR falls below a prescribed threshold using the “scanning algorithm”. If the SNR does not fall below a threshold (say 50% of the original SNR ratio), the MS continues to monitor the SNR. If the SNR falls below the threshold, then an operational mode of the MS is turned on so that the MS may communicate with a base station(s). Then via processing **915**, the MS scans, using the physical layer, to locate a new base

15 station with a higher SNR. Next, decision block **920** is invoked to determine whether or not a new base station has been located. Whenever a new base station has been located, the MS sends a request (including its shadow address and IP address) to associate with the new base station as evidenced by processing block **925**. The new base station can

20

either accept or reject the request to associate. If rejected, the MS continues to scan for a higher SNR. If accepted, the new base station updates its watch list with the shadow address and IP address information. The new base station sends an acknowledgement of receipt of the information, and the MS awaits an acknowledgement from the new base station so as to turn off the monitor mode (decision block **930**). The new base station informs the old base station of the association, via processing block **935**; details of processing by block **935** from the perspective of the base stations are covered in FIG. 11. Once soft handoff is complete, then the new base station will replace the old base station as the serving base station. During soft handoff, the packets being received from the multiple base stations can be used advantageously to determine the true contents of the packet from its replicated versions.

Now with reference to FIG. 10, there is shown flow diagram **1000** from the viewpoint a serving iBS upon power-up of a MS within the wireless region served by the iBS. Processing starts with block **1005**. Next, decision block **1010** is entered to determine whether or not this is the first power-up of the MS. If not, then there is no further processing for this MS. If this is the initial power-up, then block **1015** is entered to assign a shadow address to the MS. Then the newly assigned shadow address is inserted into the watch list of the iBS, as per processing block **1020**. Finally, the shadow address is transmitted to the MS via processing block **1025**. Processing ends with block **1030**.

Now with reference to FIG. 11, there is shown flow diagram **1100** representative of a candidate base station that is to serve the powered-up MS as it moves from a serving base station into the overlap of the wireless region of the serving base station and the candidate base station. Processing starts with block **1105**. Next, decision

5 block **1110** is entered to determine if there is an approaching MS (known via the scanning algorithm discussed above). Processing reverts to block **1110** if there is no approaching MS. For an approaching MS, via processing block **1115**, the shadow address is received from the MS. Then decision block **1120** is invoked to determine if there is a conflict with a shadow address already in the watch list of the candidate base

10 station. If there is no conflict, then the original shadow address is handled by processing block **1125** and is inserted into the watch list of the candidate base station. If there is a conflict, processing block **1135** is invoked to effect a negotiation between the serving base station and the candidate base station to determine a suitable replacement shadow address acceptable by both the serving base station and the candidate base station. Once

15 this negotiation is complete, a new shadow address is assigned via processing block **1140**, and entered into the watch list of the candidate base station (as well as replacing the one in the watch list of the serving base station as a result of the negotiation); also, the candidate base station becomes a new iBS. Processing ends with block **1145**.

20 Referring now to FIG. 12, there is shown flow diagram **1200** representative of the process for deleting a shadow address from the watch list of a base station once the MS moves outside the range of that base station. Processing starts with block **1205**. Next, decision block **1210** is entered to determine if the MS is leaving the

coverage range of the base station. If not, there is no further processing. If the MS is leaving the coverage range, then processing block **1215** is entered to signal that a handoff is to be carried out so that the new base station, differentiated from the old serving base station, will now serve the MS. Once handoff is complete, then processing block **1220** is entered to delete the shadow address from the old base station. Processing ends with block **1225**.

The technique whereby the new iBS obtains shadow address information from the old iBS, rather than from the MS directly, is now described. The teachings of FIGS. 8-12 can be readily applied to this case. It is presumed that the MS is already homing on the old iBS and is now roaming to the overlap wireless region also served by the new iBS. The MS scans to locate the new iBS. Once the new iBS is located, the MS sends a request to associate with the new iBS; the request includes the MS identifier. The new iBS sends a broadcast message to all other base stations on the subnet to determine which base station has the MS identifier in its watch list. The old iBS has the MS identifier in its watch list, so it sends a response to the new iBS with both the IP address and the shadow address contained in the old iBS's watch list. Conflicts can be resolved by interchanging messages between the old and new iBSs, which results in a unique shadow address for the MS now stored in the watch lists of both the new and old iBSs.

## 2. Soft Handoff Across Subnets

### 2.1 Packet Distribution Across Subnets

With reference to FIG. 13, there is shown system **1300** that depicts the scenario for soft handoff across Subnets. In particular, iBS A (**1311**) is connected to wireline Subnet A (**1321**), whereas iBS B (**1313**) is connected to wireline Subnet B (**1325**). In turn, Subnet A is coupled to router **1322** and Subnet B is coupled to router **1326** (it is possible, without loss of generality, that routers **1322** and **1326** may coalesce into a single router). Both routers **1322** and **1326** are then coupled to IP core network **1331**. Subnet A, Subnet B, and the IP core network may have any arbitrary network topology. In the arrangement illustrated in FIG. 13, an IP packet sent via iBS A and iBS B to MS **104** during soft handoff, as depicted by Packet A (**1341**) and Packet B (**1342**), respectively, originates from host **1305** coupled to IP core network **1331**. Accordingly, when the mobile station moves across IP Subnets, multiple copies of the same data are to be sent via multiple base stations to the mobile station (that is, Packet A and Packet B must be identical).

The manner of achieving the required packet duplication is now discussed for the following heuristic case: a so-called “nearest router” is responsible for IP packet duplication and distribution, namely with reference to FIG. 13, router **1322**, since this router is “nearest” to the MS **104** and Subnet A brought about by MS **104** initially homing on iBS A.

## 2.2 Packet Duplication

Once the soft handoff across IP Subnets A and B starts, that is, as MS 104 migrates from cell **1301** to cell **1302** in handoff region **1317**, iBS A, iBS B, and router **1322** exchange information about MS **104**. The information is in a form summarized by packet duplication information which, for the case of the nearest router **1322**, that is, the router initially handling MS **104**, is shown in Table 4.

MS Link Layer Address in Wireless Network	MS's IP Address in Subnet A	Forwarding IP Addresses in other Subnets	MS's Shadow Address in Subnet A
xxxxxxx	IP <sub>A</sub>	IP <sub>B</sub> , .....	MAC <sub>104</sub>
...	IP <sub>1</sub>	IP <sub>2</sub> , .....	NIL
...	...	...	...

Table 4

The Forwarding IP Address for a MS can be either the IP address used by the MS directly to receive IP packets in the new subnet or the IP address of an agent (e.g., a Mobile IP Foreign Agent or an iBS) in the new subnet that is responsible for intercepting the IP packets destined to the MS and then forwarding the packets to the MS.

The process of filling in, for example, row 1 of Table 4 is as follows. First, the procedure for assigning a shadow address to MS **104** in Subnet A has been discussed with reference to FIG. 8. Then the MS sends information in its watch list to nearest router **1322** so this router can be compiling the duplication table, namely, columns 1, 2, and 4 can be filled in. Referring now to flow diagram **1400** in FIG. 14, the technique for associating IP<sub>B</sub> with MS **104** as served by iBS B and then informing router **1322** of the assignment of IP<sub>B</sub> for entry into column three of Table 4 is depicted.



The process starts with processing block **1405** whereby the MS is presumed to be powered up and being served by a base station (referred to as the “old base station” below), as covered by FIG. 8. The MS continuously monitors, via decision

5 block **1410**, the incoming signal strength of the old base station to determine if the SNR falls below a prescribed threshold using the “scanning algorithm”. If the SNR does not fall below a threshold (say 50% of the original SNR ratio), the MS continues to monitor the SNR. If the SNR falls below the threshold, then an operational mode of the MS is turned on so that the MS may communicate with a base station(s). Then via processing

10 block **1415**, the MS scans, using the physical layer, to locate a new base station with a higher SNR. Next, decision block **1420** is invoked to determine whether or not a new base station has been located. Whenever a new base station has been located, the MS sends a request (including its MS identifier and its IP<sub>A</sub> address) to associate with the new base station as evidenced by processing block **1425**. The new base station can either accept or

15 reject the request to associate. If rejected, the MS continues to scan for a higher SNR. If accepted, the new base station (iBS B) sends an acknowledgement that it will associate with the MS. The MS awaits an acknowledgement from iBS B so that the MS may turn off its monitor mode (decision block **1430**). The MS and iBS B exchange a sequence of messages using, for example, the Dynamic Host Configuration Protocol, to assign the

20 new IP address IP<sub>B</sub> to the MS for use in Subnet B, as evidence by processing block **1435**. Then the MS sends a message as part of its normal interchange with iBS A to inform iBS A of the new IP<sub>B</sub> address, as per processing block **1440**. Finally, the iBS A sends a message containing the new address IP<sub>B</sub> to the nearest router (**1322**), as per processing

block **1445**, for completing the remaining entry in the Packet Duplication Table 4, namely, column three. Processing is ended by block **1450**.

Once soft handoff is complete, then the new base station will replace the old base station as the serving base station. During soft handoff, the packets being received from the multiple base stations can be used advantageously to determine the true contents of the packet from its replicated versions.

It is possible that more than one "new" candidate base station may be located during the process of "scanning" for a new base station or base stations. Each new base station independently follows a process as elaborated upon in the foregoing for the interaction between iBS A and iBS B. The interaction of only iBS A and iBS B has been discussed for the sake of specificity but without loss of generality.

Now, for any incoming IP layer packet arriving from host **1305**, router **1322** routes, via iBS A, the original Packet A destined for IP address  $IP_A$  of MS **104** using its standard routing procedure. In addition, router **1322** duplicates the packet and distributes the duplicate to MS **104** as Packet B via iBS B. In general, the procedure is that when a nearest router receives a packet destined to the IP addresses in first column of Table 4, it duplicates the packet and sends the duplicates to the IP address(es) in the third column of Table 4. Therefore multiple streams will be sent to all base stations involved in soft handoff.

In some situations, a nearest router may need to respond to the ARP REQUEST to receive the IP packets destined for mobile **104**. Therefore the shadow address of MS **104** is maintained in second column of Table 4. Also, if an iBS connects to multiple nearest routers, only one of the nearest routers is chosen to store the shadow address of MS **104**. Others will simply put NIL in the field, as exemplified by the second row of Table 4. Similarly, signaling is performed in iBSs A and B and the nearest router **1322** when soft handoff is completed, so the entry of the mobile station in a Packet Duplication table will be deleted. Such signaling can be done along with the signaling used by the mobile station to normally perform soft handoff.

Example 1. By way of specificity to summarize the procedure step-by-step, consider the arrangement of FIG. 13 wherein Packet A is sent from correspondent host **1305** attached to IP core network **1331**, that is, the packet has IP destination address  $IP_A$  and is sent from “outside” Subnet A. Since Packet A with destination address  $IP_A$  is sent outside Subnet A, it is eventually routed to router **1322**. Once router **1322** receives Packet A, it checks its Duplication Table. Packet A therefore will be duplicated with IP destination address of  $IP_B$  as depicted in the third column of Table 4, and this duplicated packet is be routed to MS **104** via iBS B. Besides, Packet A is routed to MS **104** via iBS A as a standard packet.

If there are multiple nearest routers an iBS connects to, only one of them receives the packet sent from host **1305**. Therefore only one nearest router will duplicate and distribute the packet.

As outlined above, each time a mobile station moves to a new Subnet, it must acquire a private or public IP address from a server (e.g. DHCP server or Foreign Agent) for that specific Subnet. This is part of the normal registration and configuration.

- 5 However, which IP address correspondent host **1305** should use to reach the mobile station depends on how IP-layer mobility is supported. If, for example, basic Mobile IPv4 is employed, host **1305** always uses the home address of the mobile station. The Forwarding IP Address,  $IP_B$ , for the MS in the new cell would be the new care-of address the MS obtains for receiving packets in the new subnet. The normal Mobile IPv4 Home Agent process directs a packet to the MS's care-of address currently registered with the
- 10 Home Agent. In this example, the MS can delay the Mobile IPv4 address binding operation for its new care-of address  $IP_B$  until soft handoff is completed so that the Mobile IPv4 Home Agent can continue to direct packets destined to the MS to the old base station during the handoff. Router 1322 will then duplicate the packet and forward a
- 15 copy to the new base station as described above. Upon completion of soft handoff, the MS will perform Mobile IP address binding operation for its care-of address to be used in the new cell so that later packets will be directed to this new care-of address. To reduce packet loss during the switch over from old IP address to the new IP address, removal of the Duplication Table in Router 1322 may be delayed for a pre-determined or random
- 20 time after the completion of soft handoff so that packets already sent to the old cell can continued to be forwarded by Router 1322 to the new cell even after the MS loses its radio connection with the IBS A.

Example 2. For this example, suppose for the moment that host **1305** is connected to Subnet A, that is, Packet A is sent from “inside” Subnet A, so that both router **1322** and iBS A respond to an ARP REQUEST with the mobile station’s shadow address. Therefore, Packet A eventually arrives at both iBS A and router **1322**. The one arriving at router **1322** is forwarded to the IP address(es) in third column of the Table 4 stored in router **1322**. Since this packet arriving at router **1322** is due to the entry in the Duplication Table rather than the normal routing table, router **1322** does not perform normal routing so the packet will not be sent to iBS A again. In this example, only one of the nearest routers maintains the shadow address in its Duplication Table, so that only one of them duplicates and distributes a packet.

### 2.3 Distribution of Same Data in Multiple Streams

When the nearest router sends out the duplicated IP packets, these packets have different IP addresses of the mobile station so they can be routed to different base stations. To effect soft handoff, packets must be exactly the same including any field in the header so combining of fields can be done in signal level by the mobile station. Packets duplicated and distributed from the nearest routers however are different in their destination IP addresses.

However, all the other fields other than the IP destination address are same when the nearest router duplicated the packets. As described in Section 1, the base stations perform signaling and maintain a Watch List for mobile stations involved in the soft handoff process. Base stations therefore know which mobile stations are currently in

the process of soft handoff across Subnets. The new base station then changes the IP destination address of the packet for the mobile station in the Watch Lists of the base station to the mobile station's old IP address (IP\_A). But instead of broadcasting these IP packets, the base stations will further encapsulate the IP packets to link layer frames with the link layer address in the Watch List as the destination address. These link layer frames will be sent from base stations to the mobile over the air interface without broadcasting; upon receipt by the mobile station, the link layer information is stripped from the frame, leaving only the packet with the generic broadcast address which is identical for all packets. The involved mobile station therefore will receive exactly same data from multiple base stations.

#### 2.4 Packet Selection in Reverse Link

The nearest router described above for packet distribution could be the point for packet selection as well, that is, the process of selecting one of the packets arriving from the MS via a corresponding plurality of base stations as the propagated packet.

For soft handoff in circuit cellular networks, the Nearest Router receives RLP (Radio Link Protocol) frames from multiple base stations. In addition to the payload, each RLP frame also comprises of SIR (Signal Interference Ratio), Frame Quality Indicator (FQI), Symbol Error Rate (SER), and so forth. Based on this information, one frame is singled out as the "best" frame for further distribution in the network. To preserve such layer-2 information, the iBSs encapsulate layer-2 frames to IP

packets, then send them to the Nearest Router, which then decapsulates the IP packets, selects one layer-2 frame, and assembles final IP packets. The restored packets are then routed to the correspondent host (1305) by the Nearest Router. This approach allows the iBSs to perform soft handoff in reverse link in layer-2 as that in today's cellular

5 networks. The only added function in iBSs is to encapsulate the RLP frame to IP packets. The Nearest Router, however, will need to perform decapsulation, selection, and IP assembly.

10 An alternative approach is to generate an IP packet when the iBS receives a RLP frame. The iBS generates an IP packet with the payload of the RLP frame and the decision criteria. Once the Nearest Router receives the RLP frame, it can select a packet based on IP payload, then assemble the original IP packet sent by MS and route it to the correspondent host.

15 Packet selection in the reverse direction has been described with respect to soft handoff across subnets. It is readily contemplated that an analogous description applies to packet selection in the reverse direction for soft handoff within a subnet.

### 3. Data Content Synchronization

20 One potential way to achieve data content synchronization at the MS is to have all iBSs transmit copies of the same packet to the mobile station at precisely the same time. However, scheduling the precise timing for simultaneous transmissions of IP packets on different IP devices (in this case, iBSs) is very difficult to implement in a real

IP network.

This Section describes a new IP-layer procedure, referred to as the “Fluid Synchronization” method, performed by the iBSs to ensure that the data arriving at the MS at the same time from multiple iBSs are copies of the same data. The method is an IP-layer procedure and is therefore independent of the link layer protocols used in the radio system. The procedure is performed by iBSs rather than by the MS, which avoids any modification to the MS.

Rather than trying to schedule the precise timing for simultaneous IP packet transmissions on multiple iBSs, the methodology ensures that the streams of layer-2 data blocks sent by multiple iBSs to the MS are “matchable streams”. Matchable streams are streams of layer-2 blocks (or more precisely, the physical layer data resulting from these blocks) that can be correctly matched and combined by the MS using today’s radio technologies (e.g., a RAKE receiver as discussed in the reference by V.K Garg, entitled “IS-95 CDMA and cdma 2000:Cellular/PCS Systems Implementation”, pp. 60-62, published by Prentice-Hall, 2000).

Suppose that the streams of IP packets sent by different iBSs to the MS have either no gaps (i.e., no missing IP packets) or identical gaps. Then, the layer-2 data block streams from the iBSs to the MS will be matchable if, for any  $k$ , the  $k^{\text{th}}$  layer-2 data block sent by both iBSs to the MS contains the same amount of payload (i.e., have the



same length). The matching layer-2 data blocks (i.e., data blocks that are copies of the same data) from different iBSs do not have to arrive at the mobile at precisely the same time. The mobile's radio system can synchronize these data blocks using today's radio channel synchronization techniques, as long as the delay jitters are not excessively large, which usually is one time slot length of a frame.

It is also important to note that generating matchable streams of layer-2 data blocks does not require each iBS to send copies of the same IP packet to the layer-2 protocol at precisely the same time for delivery to the MS. Furthermore, matchable streams of layer-2 data blocks can be generated by performing only IP-layer processing on the iBSs alone.

FIG. 15 illustrates how matchable streams of layer-2 data blocks can be generated when the IP packets are sent by different iBSs to the layer-2 protocol on their radio interfaces at different times for delivery to the MS. With reference to FIG. 15, there is shown a stream of numbered packets, designated "1" (1511), "2", "3", "4", "5", "6", and so forth, arriving at, for example, iBS A of FIG. 13. Similarly, the same stream of packets arrives at iBS B, wherein packet 1521 is the first packet in the stream. Note that the packets arrive at the respective iBSs at different times (time line 1531-1 is used to reference packets for iBS A, whereas replicated time line 1531-2 is used for packets arriving at iBS B). IP packets are sent to the link layer for delivery over-the-air to the MS at the times shown by the downward arrows on the respective time lines; for example, packet 1511 is transmitted at the time shown by arrow 1512, and packet 1521 is

transmitted at the time shown by arrow **1522**. The over-the-air link layer receives the packets as data blocks and fills the data blocks into link layer frames. The over-the-air link layer frames corresponding to iBS A are shown by the stream of frames starting with **1513**, **1514**, and so forth. Similarly, the over-the-air link layer frames corresponding to iBS B are shown by the stream of frames starting with **1523**, **1524**, and so forth. Frames **1513** and **1523** are blank, and they are shown primarily to demonstrate that there is a random delay (**1532**) between the two streams of frames. As long as the random delay is within the synchronization capability of the receiver technique, fluid synchronization can be effected. The “sideways” arrows, such as arrow **1515**, depict when the iBS A IP packets sent to the link layer for delivery over-the-air have been fully processed and are encapsulated into frames. Thus, frame **1514** encapsulates the data blocks derived from packets “1” and “2” from iBS A. Similarly, the next frame encapsulates data from packets “2” and “3”. Because the data block associated with packet “5” undergoes a significant delay in delivery, the data block for packet “5” is not ready for encapsulation until the fifth frame. Moreover, this data block is too long for a single frame, so it is used to partially fill the next succeeding frame, along with data from packet “6”. Finally, another frame is needed to complete delivery of packet “6” because of its length.

Similarly, the “sideways” arrows, such as arrow **1525**, depict when the iBS B IP packets sent to the link layer for delivery over-the-air have been fully processed and are encapsulated into frames. Thus, frame **1524** encapsulates the data blocks derived from packets “1” and “2” from iBS B. Similarly, the next frame encapsulates data from packets “2” and “3”. Because the data block associated with packet “5” undergoes a

significant delay in delivery, the data block for packet “5” is not ready for encapsulation until the fifth frame. Moreover, this data block is too long for a single frame, so it is used to partially fill the next succeeding frame, along with data from packet “6”. Finally, another frame is needed to complete delivery of packet “6” because of its length.

5

Based on the observations described above, a Basic Synchronization Procedure (BSP) is as follows (the Radio Link Protocol (RLP) is used as an exemplary radio layer-2 protocol in the following discussions). Starting from the delivery of the same IP packet to the mobile, each iBS will

10

- 1) Use RLP frames of identical length
- 2) Deliver only fully filled RLP frames to the MS unless
  - a) a timer  $T_p$  expires, or
  - b) instructed by the upper layer (i.e., the IP layer) to send the current data.

15

In real networks, several events may cause a loss of data content synchronization when the above method is used. For example, gaps may randomly occur in the IP packet streams sent by different iBSs to the mobile. Also, when timer  $T_p$  times out or when the IP layers on different iBSs instruct their layer 2 to send the current available data, the resulting layer-2 data blocks from different iBSs may not contain an identical amount of payload.

20

To correct for these events, a data content re-synchronization procedure is described that can quickly bring the multiple layer-2 data block streams from different

iBSs back to synchronization when loss of data content synchronization occurs. The foundational principle is that the iBS which detects (or suspects) a loss of data content synchronization will negotiate with the other iBSs to restart the BSP procedure from a new IP packet.

5

This following describes the data content re-synchronization procedure using packet gaps as an exemplary cause of loss of data content synchronization. To help iBSs detect gaps in IP packet streams, the source or the entity responsible for packet distribution can number the packets (e.g., using the 16-bit identification field or an optional field in the IP header) and increment the packet stream number by one each time an IP packet is sent.

10

15

20

The depiction of FIG. 16 is a pictorial representation of the results to be determined by the re-synchronization procedure. In particular, FIG. 16 illustrates two streams of frames sent to the MS from iBS A and iBS B, namely, the stream from iBS A encapsulating packets 1611, ..., 1612, and the stream from iBS B encapsulating packets 1621, ..., 1622, ..., 1623. The frames from iBS B are delayed relative to the frames from iBS A, as already pointed out in FIG. 15. In the depiction of FIG. 16, the frame containing packet "3" from iBS A has been "lost" in the over-the-air delivery from iBS A to the MS. Data content resynchronization is regained at the RLP frames 1612 and 1623, respectively, for iBS A and iBS B, based upon the above data content synchronization procedure now discussed in steps (a)-(f) below.

Suppose that iBS A detects a gap between packet  $k$  and packet  $m$  ( $m > k$ ) in the stream of IP packets destined to the MS. That is, iBS A has received packets  $k$  and  $m$  but has not received any packet between packets  $k$  and  $m$ . iBS A will initiate the following data content re-synchronization procedure, discussed with reference to flow diagram 1700 of FIG. 17 (as a shorthand, a number  $x$  in a layer-2 frame indicates that the layer-2 frame contains data from the IP packet with stream number  $x$ ):

(a) **1705**: iBS A requests iBS B to re-start the BSP procedure from a packet  $q$  ( $q \geq m$ ).

(b) **1710**: iBS A immediately sends to the MS all the packets it has received before packet  $q$  without enforcing the BSP rules and halts the delivery of packet  $q$  and the packets arrived after packet  $q$ .

(c) **1715**: determine if iBS B can (or has a high level of confidence that it can) re-start data synchronization as requested by iBS A (e.g., when iBS B has received packet  $q$  and has not yet sent it to the MS, or has not yet received packet  $q$ ).

(d) if so, iBS B will positively acknowledge iBS A's request (**1720**). Then, iBS B will immediately send to the MS all the packets it received before packet  $q$  without enforcing the BSP rules (**1725**). iBS B will then restart the BSP procedure from packet  $q$  (**1730**). In other words, layer-2 transmission of packet  $q$  will start from the beginning of a new layer-2 frame after the packets before  $q$  have been delivered. Further, starting from packet  $q$ , layer-2 transmission will follow the BSP rules.

(d) **1735**: upon receiving positive acknowledge from iBS B, iBS A will restart the BSP procedure from packet  $q$ .

(e) if iBS B cannot re-start re-synchronization as requested by iBS A (e.g., iBS B

may have already sent packet q to the MS), iBS B will select a new packet r after packet q ( $r > q$ ) and requests iBS A to start re-synchronization at packet r (1740).

(f) both iBS A and iBS B start BSP procedure commencing with packet r (1745).

5           The re-synchronization procedure described above can be used to re-gain data content synchronization when loss of data content synchronization is caused by other events besides gaps in IP packet streams. If, for example,  $T_p$  on iBS B expires before a RLP frame is fully filled, iBS B will send the partially filled frame to the MS. However, this may lead to loss of data content synchronization. To re-gain data content  
10           synchronization, iBS B can request iBS A to re-start the BSP procedure from a new packet. To reduce the impact of loss of data content synchronization caused by unexpected events, the iBSs currently involved in soft handoff may periodically re-start the data content re-synchronization procedure.

#### 15   4. Smooth Handoff

          This Section discusses how to leverage the Shadow Addresses maintained in each base station to achieve “smooth handoff”. Smooth handoff means that the mobile station still can transmit and receive packets while it is performing handoff. Ideally there will be no delay and packet loss in smooth handoff. Again, a macro-diversity system is  
20           assumed, that is, the system is such that that a mobile station is capable of transmitting and receiving data from multiple base stations at the same time. Although smooth handoff in a macro-diversity system is feasible in current circuit-based centralized cellular

systems, the focus of this Section is on packet-based IP networks in which there is no central controller. In addition, the subject matter in accordance with the present invention has the following unique features:

(a) the same algorithms and table can be used for both link- and network- layer handoffs. The base station does not need to distinguish the type of handoff, and does not need to run two handoff algorithms. This makes the IP-based base station efficient and also reduces the cost.

(b) the same algorithms and table can be used for mobile stations served by multiple base stations either on same or different IP subnet.

(c) no signaling at or above the IP layer is required.

(d) a mobile station does not have to use an additional IP address.

(e) no modification to the mobile station is required. Base stations maintain the necessary table, cache the shadow addresses, and perform extra techniques for handoff.

(f) the smooth handoff technique scales well for large networks.

#### 4.1 Smooth Handoff within a Subnet

Base stations perform the algorithms in Sections 1.1, 1.3 and 1.5 to assign and insert a shadow address in the Watch Lists for the mobile station. Base stations then respond to an ARP REQUEST when there is an IP packet destined to the mobile station. Since the base stations involving in the smooth handoff have the same shadow address for the mobile station, the mobile station will receive the IP packets from at least one base station. Therefore smooth handoff can be achieved. The entry of the mobile station in the old base station will be deleted once the handoff is done. The mobile station then will

receive packets only from one base station.

#### 4.2 Smooth Handoff Across Subnets

For handoff across different subnets, base stations again perform the same algorithms in Sections 1.1, 1.3 and 1.5. The shadow addresses used by the same mobile station in cells belonging to different IP subnets may be the same or different. Depending on specific IP-layer mobility management methods, IP packets may be sent to a single or multiple base stations. In particular, if soft handoff in the IP layer is deployed, IP packets will be sent to multiple base stations. Smooth handoff can be achieved using the same method described in the Section 4.1. If soft handoff is not deployed in the IP layer, the IP packets will be destined to only one base station (i.e., either the new or the old base station). Either the new or the old base station will be able to correctly respond to the ARP REQUEST from any other network device (e.g., an IP router or another iBS) that wants to send IP packets to it. This is because either one of the base stations will already have the mobile station's shadow address in its Watch List. Therefore, the IP packets can reach the mobile station from either one of the base stations. Base stations do not need to do any extra signaling with other base stations in either the link- or the network- layer for carrying out handoff. Furthermore, only one handoff is needed when mobile station moves across IP subnets. Thus, smooth handoff is achieved easily in both link- and network- layers.

Also, by way of reiteration, each time when the mobile station moves to a new subnet, it must acquire a private or public IP address from a server (e.g. DHCP



server or Foreign Agent) for that specific subnet. This is part of the registration and configuration. Which IP address the CH should use to reach the mobile station depends on how location update is performed. If basic Mobile IPv4 is employed, for example, CH always uses the home address of the mobile station. The normal Home Agent process  
5 directs a packet to old (or home) IP address before handoff, that is, registration of new IP address with the Home Agent is delayed until soft handoff is completed.

10 In some cases, the mobile station may perform smooth handoff with multiple base stations. Not all of these cells may be on the same IP subnet. The algorithms still apply in this case and smooth handoff can be achieved as well.

15 Although the present invention have been shown and described in detail herein, those skilled in the art can readily devise many other varied embodiments that still incorporate these teachings. Thus, the previous description merely illustrates the principles of the invention. It will thus be appreciated that those with ordinary skill in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody principles of the invention and are included within its spirit and scope. Furthermore, all examples and conditional language recited herein are principally  
20 intended expressly to be only for pedagogical purposes to aid the reader in understanding the principles of the invention and the concepts contributed by the inventor to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects,

and embodiments of the invention, as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents as well as equivalents developed in the future, that is, any elements developed that perform the function, regardless of structure.

In addition, it will be appreciated by those with ordinary skill in the art that the block diagrams herein represent conceptual views of illustrative circuitry embodying the principles of the invention.